



TABEO-2/S/ZIRKON-120



TABEO-2/S/ZIRKON-120



▼ **High purity silicon-carbide heating elements**

▼ **Maximum temperature 1550°C**

▼ **Service programs**

A - Temperature control*

C - Purge heating chamber

▼ **Program control**

7-segment LED

4 stages

9 program capacity

Special functions


▼ **Thermocouple PtRh-Pt, type S**

▼ **Maximum heating rate 25°C/min**

▼ **Temperature accuracy at 1500°C +/- 3 °C**

▼ **Timer function**

* only in conjunction with test-kit



RS-232 Interface allows you to record real time program data for analysis or compliance



Technical data TABEO-2/S/ZIRKON-120

Heating-chamber capacity 3 trays Ø 120x30 mm

Power max. 2000 W

Voltage range; frequency 200 – 240 V; 50/60 Hz

Weight 85 kg





Dimensions W/D/H 480/460/680 mm

Technical data



TABEO-2/S/ZIRKON-120
720100002

Details ✓ standard ✗ not compatible ● optionally available

Technical information		
Heating-chamber height	mm	92
Max. heating-chamber capacity	number of trays	 3 x 120/30 mm
Heating system		
Process capability		
Max. temperature		
Heating elements	type	
	number	4
Process times CLASSIC [1*]		
Max. programmable heating rate	°C/min	25
Shortest heating period to 1.500°C at 230V	min	58
Shortest cooling period to 300°C	min	143
Process duration (incl. holding time 30 min)	min(h)	231(3,9)
Process times SPEED [1*]		
Max. programmable heating rate	°C/min	✗
Shortest heating period to 1.500°C at 230V	min	✗
Shortest cooling period to 750°C	min	✗
Process duration (incl. holding time 30 min)	min(h)	✗
Programm control		
7-segment LED		✓
4-lines LCD		✗
Number of programmable stages		4
Program capacity		9
	Number of fixed programs	✗
	Number of customizable programs	9
Special programs		
Drying		✗
Heating-up ventilated		✗
Service programs		
A-Temperature control [2*]		✓
C-Purge heating chamber		✓
E-Regenerate heating elements		✗
Thermocouple		
PtRh-Pt, type S		✓
Special functions		
Emergency cooling system		✗
RS 232 interface		●
Door lift		✗
Shielding-gas supply		✗
Timer function		✓
Technical data		
Power max.	W	2000
Voltage range; frequency	V; Hz	200-240; 50/60
Weight	kg	85
Dimensions W/D/H	mm	480/460/680

[1*] Process values: Sintering temperature = 1500°C; holding time = 30min; 1 x sintering tray [2*] only in conjunction with test-kit

Scope of delivery



TABEO-2/S/ZIRKON-120
7201000002

- ✓ standard
- optionally available
- optionally available, but with reservations
- ✗ not compatible

Sintering tools		
8201000001	Sintered corundum AL, 4-6; 200g	●
8201000002	Sintering beads YTZ, 2.0; 200g	●
8201000003	Sintering beads YTZ, 1.25; 280g	●
8201000004	Sintering granulate YTZ; 200g	✓
8201000008	Sintering tray, 120/30	✓
8201000009	Sintering tray, 120/35; ventilated	●
8201000010	Sintering tray lid, 120/4	✓
8201000011	Sintering tray, intermediate ring 120/35	●
8201000014	Sintering tray SPEED, 120/30; slotted	●
8201000015	Sintering tray SPEED, 120/30 (kit)	●
8201000018	Sintering base plate SPEED, 120/15	●
8201000019	Sintering base plate SPEED, top ring 120/15	●
8201000021	Sintering disc, 120/12	●

Accessories		
8202000004	Removal fork T-2	✓
8202000005	Diamond whetstone; for sintering discs	●
8202000008	Power cord EU, C19; 16A	✓
8202000009	Power cord USA, C19; 16A	●
8202000010	Power cord GB, C19; 13A	●

**CONSISTENT.
RELIABLE.
PRECISE.**



MIHM-VOGT GmbH & Co. KG
Friedrich-List-Straße 8
76297 Stutensee-Blankenloch
Germany

Web www.mihm-vogt.de
Mail info@mihm-vogt.de